

PRODUCT DATA SHEET

2024-04-09



Article number:

5810005233ESD1

Swivel castor 100 mm, PA6-wheel, conductiv, total stop brake

Swivel bracket. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Center hole fitting. Wheel axle with nut. Wheel with roller bearing, nature PA6, threadguards. Ball bearing. ESD. Total stop brake. Conductivity : $\leq 1\text{ M}\Omega$



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	100 mm
Totalt height	132 mm
Load Capacity (dynamic)	170 kg
Castor model	Brake
Fitting	Centre hole
Material Tread	Nylon PA6
Bearing	Ball bearing
Thread hardness (Shore°)	98° Shore A
Centre Bolt Hole	12.4 mm
Brake	Total brake
Width of tread	36 mm
Material Hub	Nylon PA6
ESD	Yes
Color Tread	Grey
Material Type	RoHS (EU) - Approved
Offset	41 mm
Material Thickness Bracket	2,5 mm
Swivel radius	129 mm
Product Weight	0,94 kg
Temperature Range	-30°C to +70°C
ESD	Conductive ($\leq 1\text{ M}\Omega$)

Numeric values in the technical specification can be nominal/rounded to the cneares standard dimension. To see exact values, please use the drawing.