

PRODUCT DATA SHEET

2024-04-11



Article number:

5810005433ESD1


Swivel castor 100 mm, gray ESD PUR-tire, total stop brake

Housing made of zinc-chromatized, pressed steel with double ball race swivel head with centre hole, screwed wheel axel. Total stop brake. Wheel with precision ball bearing and grey PUR-tyre, Hub och washer in gray PA6. ESD, Conductivity : $\leq 1\text{ M}\Omega$



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	100 mm
Totalt height	132 mm
Load Capacity (dynamic)	200 kg
Castor model	Brake
Fitting	Centre hole
Material Tread	Polyurethane
Bearing	Ball bearing
Thread hardness (Shore°)	98° Shore A
Centre Bolt Hole	12.4 mm
Brake	Total brake
Width of tread	36 mm
Material Hub	Nylon PA6
ESD	Yes
Color Tread	Grey
Material Type	RoHS (EU) - Approved
Offset	41 mm
Material Thickness Bracket	2,5 mm
Swivel radius	129 mm
Product Weight	0,94 kg
Temperature Range	-30°C to +70°C
ESD	Conductive ($\leq 1\text{ M}\Omega$)

Numeric values in the technical specification can be nominal/rounded to the cneares standard dimension. To see exact values, please use the drawing.