

PRODUCT DATA SHEET

2024-04-10



Article number:

5A10005912GSX

Braked castor 100 mm, total stop brake, elastic rubber-tyre, stainless

Swivel bracket with total stop brake. Pressed stainless steel with double ball race swivel. Center hole fitting for M12 screw. Wheel axle with nut. Wheel with grey elastic rubber-tyre. Hub made of black Nylon/PA6. Plain bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	100 mm
Totalt height	128 mm
Load Capacity (dynamic)	150 kg
Castor model	Brake
Fitting	Centre hole
Material Tread	Elastic Rubber
Bearing	Plain bearing
Thread hardness (Shore°)	70° Shore A
Centre Bolt Hole	13 mm
Brake	Total brake
Width of tread	36 mm
Hub Hole Diameter	8 mm
Material Hub	Nylon PA6
Stainless	Yes
Fork Width	46 mm
Dyn. Load Capacity (4km/)	150 kg
Color Tread	Grey
Material Type	RoHS (EU) - Approved
Offset	46 mm
Material Thickness Bracket	2 mm
Swivel radius	124 mm
Product Weight	0,83 kg
Temperature Range	-20°C to +60°C

Numeric values in the technical specification can be nominal/rounded to the nearest standard dimension. To see exact values, please use the drawing.